MEMORANDUM FOR RECORD:

SUBJECT

: Viets to Haller, Raymond and Brown, Inc.

on The February 1959

ATTENDERS

: Measrs.

25X1

25X1

25X1

9...

1. A suggestion was made how to mount the second Ampex 814 tape recorder on the A frame and steps were taken to modify the System to accommodate the two (2) tape recorders.

stated that 400 cycle signals did not interfere with normal operation of the HRB 188 video processing unit. The 400 cycle signal would lower the system sensitivity but will not generate a false alarm. Signals from 500 cycles to 3 ke at 500 cycles multiples and in addition to another signal at 250 ke will generate a false alarm.

- 3. A complete System VII test will be performed at HRB before the unit is shipped.
- 4. Progress of the telemetry transmitter at Edwards is progresto handsing satisfactorily. Arrangements were made for carry the HRB telemetry simulator back with him.
- 5. Flight test of the System was discussed. The System will be checked out in the following manner:
 - 5.1. Bench test
 - 5.2. Flight line (installed in A/C)5.3. Flight over field

 - 5.4. Flight test at altitude and range (65,000 ft. 600 nautical mile range)
- 6. A demonstration was given with a bench lash-up of part of System VII. Turn on sensitivity of better than minus 100 dbm was

25 YEAR RE-REVIEW

V. OPET



CHAL-0593-59 Cy. 2 of 3 Cys.

observed with a dynamic range better than 40 db.

- 7. HRB still does not have a temperature and/or pressure chamber. They have not temperature cycled their sync extractor. They were able to adjust the unit at 70° F and bring the temperature up about 15° F before failure. (The unit will be thermostatically controlled in the A/C).
- 8. The sync extractor and simulator are quite critical units and their adjustments are very touchy. It also appears, according to HRB, that the simulator has to be readjusted to operate with a specific extractor.
- 9. HRB sync extractor borrowed from Commo, was tested after readjusting both the simulator and the extractor. The unit functioned normally in all respects. The same test setup at JPL was used.
- 10. The System is on schedule and should be ready for shipment on 2 March 1959.

11.	is taking steps t	to bommer a Collin	ast I be stome?
wideownd transmitter	r receiver. This	Will be fitted to	the A/C in
Illight test to deter	rmine the feasibil	ity of maine this	- Acut ment
TOL # AOICS STELL LA	irn-on procedure.	It will probably	t be tested to
a range of 1200 naut	ticul miles.	}	nd negree to

25X1

EMINT STAFF

Distribution:

Copy 1 - System VII
2 - Project Chrono
3
ESO:
ang (10 Mar 59)

25X1

25X1

25X1